



# Reliant Propane Burnishers

**Brilliant results at amazing speed.**

## RELIABLE • PRODUCTIVE • ECONOMICAL

Choose from 13 hp to 17 hp propane powered engines.

Discover the superior performance and productivity built into the design of Aztec Reliant buffers. From an offset body that allows easy access under racks and in corners to the unique pad angle that eliminates side torque and dramatically increases head pressure, the economical Reliant buffer is a time and money saver. Available from stock with Kawasaki engines.

- Rugged steel and cast aluminum body
- Unique pad angle design
- Right side offset machine body
- 13 hp & 17 hp Kawasaki engine
- 110 volt starter or 12 volt battery with key switch option
- Low oil shut down
- Hour Meter/Tachometer
- Safety regulator fuel system
- UL and CGA approved, meets CARB and EPA emissions standards
- 2-year warranty



**Made in the USA**

Reliant is an unsurpassed value due to its **Simplicity** of design and productivity. With fewer parts and longer service intervals, the machine's design minimizes field problems and expensive downtime. Dependability and ease of operation make all of Aztec's high speed floor care equipment a must for the growing Building Service Contractor or in-house professional.

Phone 215.393.4700 • Fax 215.393.4800  
Call Toll Free 1-800-331-1423

[www.aztecproducts.com](http://www.aztecproducts.com)



21" Rated 25,000 Sq. Ft./hour		
Specifications	Kawasaki 13hp	Kawasaki 17hp
Pad Size	21"	21"
Pad Speed	2000 RPM	2000 RPM
Work Rating	25,000 sq. ft.	25,000 sq. ft.
Engine Speed	3400 RPM	3400 RPM
Horsepower	13 hp	17 hp
Fuel System	regulator system	regulator system
Oil Safety System	low oil shut down	low oil shut down
Starter (Std.)	110 volt	12 volt battery w/key
Starter (optional)	12 volt battery w/key	— —
Propane Tank	steel safety fill	steel safety fill
Width	23"	23"
Length	42"	42"
Height	28"	28"
Weight	189 lbs.	197 lbs.
Sound Level	80-82 db	80-82 db
Vibration	less than 2.5 mm	less than 2.5 mm
Deck	steel & cast aluminum	steel & cast aluminum
Handle	adjustable steel	adjustable steel
Engine Warranty	2 years	2 years

24" Rated 29,000 Sq. Ft./hour		
Specifications	Kawasaki 13hp	Kawasaki 17hp
Pad Size	24"	24"
Pad Speed	1800 RPM	1800 RPM
Work Rating	29,000 sq. ft.	29,000 sq. ft.
Engine Speed	3400 RPM	3400 RPM
Horsepower	13 hp	17 hp
Fuel System	regulator system	regulator system
Oil Safety System	low oil shut down	low oil shut down
Starter (Std.)	110 volt	12 volt battery w/key
Starter (optional)	12 volt battery w/key	— —
Propane Tank	steel safety fill	steel safety fill
Width	25"	25"
Length	46"	46"
Height	30"	30"
Weight	215 lbs.	215 lbs.
Sound Level	80-82 db	80-82 db
Vibration	less than 2.5 mm	less than 2.5 mm
Deck	steel & cast aluminum	steel & cast aluminum
Handle	adjustable steel	adjustable steel
Engine Warranty	2 years	2 years

27" Rated 33,000 Sq. Ft./hour		
Specifications	Kawasaki 13hp	Kawasaki 17hp
Pad Size	27"	27"
Pad Speed	1700 RPM	1700 RPM
Work Rating	33,000 sq. ft.	33,000 sq. ft.
Engine Speed	3600 RPM	3600 RPM
Horsepower	13 hp	17 hp
Fuel System	regulator system	regulator system
Oil Safety System	low oil shut down	low oil shut down
Starter (Std.)	12 volt battery w/key	12 volt battery w/key
Propane Tank	steel safety fill	steel safety fill
Width	29"	29"
Length	47"	47"
Height	30"	30"
Weight	215 lbs.	228 lbs.
Sound Level	80-82 db	80-82 db
Vibration	less than 2.5 mm	less than 2.5 mm
Deck	steel & cast aluminum	steel & cast aluminum
Handle	adjustable steel	adjustable steel
Engine Warranty	2 years	2 years